



TORO® DINGO TX 700

COMPACT UTILITY LOADERS

Designed to give you more power in a compact package, the Toro® Dingo® TX 700 expands labor savings beyond just homeowner projects. This no-nonsense workhorse packs 700 lbs of rated operating capacity in a smaller footprint, so it's ideal for projects where homeowners and contractors are working in confined spaces. It also features patented Dingo TX 1000 traction controls that are easy to use, and a dedicated stand-on platform for increased operator comfort and visibility. And with dozens of compatible attachments, it's a versatile machine you can utilize for a wider range of jobs. With just the features you need, plus the familiarity and comforts of a Toro Dingo, it's an excellent solution to increase labor savings.

FEATURES



COMPACT DESIGN

Great for homeowners and contractors who need to access smaller spaces

TRACK SYSTEM

This industry-accepted design offers a less aggressive tread pattern

EASY-TO-USE CONTROLS

Effortless traction controls are easy to use for all-day productivity.



STAND-ON PLATFORM

The dedicated platform on a compact frame. Plus, the spring loaded AUX foot pedal increases foot space

TORO® DINGO TX 700

SPECIFICATIONS - PRELIMINARY AND SUBJECT TO CHANGE

		DINGO TX 700 (MODEL 22351)	DINGO TX 700 WIDE TRACK (MODEL 22352)
ENGINE	Engine	24.5 HP Yanmar 3TNV80F	
	Air Filter	Remote single element	
	Cooling System	Combo downflow radiator and oil cooler	
	Fuel Tank	5.5 gallons (20.8 liters)	
	Oil Capacity	3.6 quarts (3.4 liters)	
HYDRAULIC SYSTEM	Hydraulic Pressure	3,000 PSI	
	Hydraulic Flow	Traction: 14.5 gpm (each pump) Auxiliary: 13.7 gpm	
	Reservoir Capacity	10 gallons (37.9 liters)	
TRACKS	Standard	Camsco B-Tread	Camsco Turf Friendly
	Traction	Dual hydrostatic pump	
DIMENSIONS	Track Dimensions	5.4" x 126.6" (13.7 cm x 321.6 cm)	9.1" x 126.6" (23.1 cm x 312.6 cm)
	Wheelbase	39" (99 cm)	
	Ground Clearance	5.25" (13.3 cm)	
	Overall Dimensions (WxLxH) With Bucket	34.2" x 102.8" x 55.3" (86.9 x 261.1 x 140.5 cm)	41.4" x 102.8" x 55.3" (105.2 x 261.1 x 140.5 cm)
	Overall Dimensions (WxLxH) Without Bucket	34.2" x 82" x 55.3" (86.9 x 208.3 x 140.5 cm)	40.2" x 82" x 55.3" (102.1 x 208.3 x 140.5 cm)
	Maximum Operating Height	97" (246.4 cm)	
	Hinge Pin Height	73.5" (186.7 cm)	
	Dump Height	52.9" (134.4 cm)	
	Dump Angle	42-degrees	
	Reach - Fully Raised	31" (78.7 cm)	
Ground Speed	4.0 mph (6.4 km/h)		
Weight	2,756 lbs (1250 kg)	2862 lbs (1298 kg)	
Tip Capacity	2,000 lbs (907 kg)	2,023 lbs (918 kg)	
Rated Operating Capacity (35% of Tip Capacity)*	700 lbs (317.5 kg)	708 lbs (321.1 kg)	
Ground Pressure	13 PSI	8 PSI	

*Per ISO 14397-1

