



TORO® DINGO® TX 1300

COMPACT UTILITY LOADERS

Ideal for landscape, hardscape and tree care jobs, the TX 1300 brings a new combination of power, reach and convenient control to the Toro® Dingo® lineup. With a 37 hp Yanmar® Tier IV diesel engine and 1,300 lbs of rated operating capacity, it's the user-friendly workhorse you need to save time. The exclusive INTELLESCOPE® loader arm with SmartLoad adds 26" of reach, and the telescoped hinge-pin height of 109" means you can lift loads up and over the side of a dumpster or truck for maximum productivity. Plus, you can operate the Toro patented traction controls with one hand and thumb-controlled telescoping extension and auxiliary functions (in the loader arm control) with the other to pick, place and dump materials with ease all day long.

FEATURES

INTELLESCOPE LOADER ARM

Featuring SmartLoad for a hinge-pin height of 109" which adds 26" of reach over other compact utility loaders

QUICK COUPLER SYSTEM

Pressure relieving quick coupler system makes connection of attachments easier

INTEGRATED AUXILIARY

Integrated auxiliary operation in loader arm control eliminates secondary hydraulic operation



DURABLE LOADER ARM

The improved q-tach casting allows for a more durable loader arm design



AUXILIARY PEDAL

User friendly auxiliary pedal on an enlarged operator platform improves ease of engagement

TORO® DINGO® TX 1300

SPECIFICATIONS

		DINGO TX 1300 (MODEL 22370)
ENGINE	Engine	37 HP (27 kW) Yanmar® diesel
	Air Filter	Remote dual element
	Cooling System	Combo downflow radiator and oil cooler, independent fuel cooler
	Fuel Tank	11 gallons (42 liters)
	Oil Capacity	5 quarts (4.7 liters)
HYDRAULIC SYSTEM	Hydraulic Pressure	3,200 PSI
	Hydraulic Flow	Traction: 13.4 gpm (each pump) Auxiliary: 14.3 gpm
	Reservoir Capacity	9.2 gallons (34.8 liters)
TRACKS	Standard	MERT track with "TF" style tread
	Traction	Dual hydrostatic pump
DIMENSIONS	Track Dimensions	126.6" x 9.1" (322 cm x 23 cm)
	Wheelbase	39" (99 cm)
	Ground Clearance	5.9" (15 cm)
	Overall Dimensions (WxLxH) With Bucket	46" x 103.1" x 56.5" (116.8 x 262 x 143.5 cm)
	Overall Dimensions (WxLxH) Without Bucket	46" x 84.9" x 56.5" (116.8 x 215.6 x 143.5 cm)
	Maximum Operating Height	133" (337.8 cm)
	Hinge Pin Height	89.4" (227 cm) - retracted 109.2" (277.4 cm) - extended
	Dump Height	90.7" (230.3 cm) extended, 70.9" (180 cm) retracted
	Dump Angle	38-degrees
	Reach - Fully Raised	26.7" (67.8 cm)
Ground Speed	4.7 mph (7.6 km/h)	
Weight	3,858 lbs (1,750 kg)	
Tip Capacity	3,714 lbs (1,685 kg)	
Rated Operating Capacity (35% of Tip Capacity)*	1,300 lbs (590 kg) - retracted 618 lbs (280 kg) - extended	
Ground Pressure	5.5 PSI	

*Per ISO 14397-1

